



AUTOMOTIVE NORDIC

Product List



Automotive

NOx

PRODUCT	DESCRIPTION	APPLICATION	PACKAGING
AdBlue	Urea 32%	Adblue converts harmful NOx from diesel vehicles' exhaust systems to harmless nitrogen and water vapor, thereby significantly reducing emissions of nitrogen oxides (NOx). Approved by VDA.	Can
Urea Solution 40% High Pure Urea Solution 40%	Urea 40%	Reduces NOx emission from marine vessel or diesel exhaust systems.	IBC1.000 ltr. Bulk

SOx			
PRODUCT	DESCRIPTION	APPLICATION	PACKAGING
Sodium hydroxide 50%	Caustic soda solution 50% Chemical name: NaOH	Sodium hydroxide 50% is used in the marine vessel's scrubber system. Reduces SOx emission from marine vessel or diesel exhaust systems.	IBC1.000 ltr. Bulk
Caustic Soda Pearls	Caustic soda solid form Chemical name: NaOH	Caustic Soda Pearls is used in the marine vessel's scrubber system. Reduces SOx emission from marine vessel or diesel exhaust systems.	Bag 25 kg. Big bag 500 kg / 1.000 kg.
Sodium bicarbonate	Sodium bicarbonate powder Chemical name: NaHCO3	Sodium bicarbonate is used in the marine vessel's scrubber system. Reduces SOx emission from marine vessel or diesel exhaust systems.	Bag 25 kg. Big bag500 kg / 1.000 kg. Bulk
Sodium carbonate	Sodium carbonate powder/ granulate Chemical name: Na2CO3	Sodium carbonate is used in the marine vessel's scrubber system. Reduces SOx emission from marine vessel or diesel exhaust systems.	Bag 25 kg. Big bag500 kg / 1.000 kg. Bulk
Magnesium oxide	Magnesium oxide powder Chemical name: MgO	Magnesium oxide is used in the marine vessel's scrubber system. Reduces SOx emission from marine vessel or diesel exhaust systems.	Bag 25 kg. Big bag500 kg / 1.000 kg. Bulk



Automotive

FUELS & LUBRICANTS

RELIANT® Alkyalte Gasoline -2 Stroke

RELIANT® Alkylate Gasoline -4 Stroke

RELIANT® Racing Fuel

RELIANT® HVO Renewable Diesel

RELIANT® BIO Chain Saw Oil

DESCRIPTION

Reduces impact on the environment. Cleanest petroleum based product possible. Better for the machines and your health. +2% full synthetic oil.

Reduces impact on the environment. Cleanest petroleum based product possible. Better for the machines and your health.

Maximizes your engine's performance and provides optimal conditions for your engine with the highest possible octane number RON 102 in accordance with FIA guidelines.

100% renewable diesel. Behaves exactly like fossil diesel and offers a CO2 reduction of 40-80% compared to fossil products. Does have extra long shelf life and meet all the requirements of professional users.

Optimal adhesion properties - minimizing friction, spillage and wear. 100% biodegradable and extracted from specially selected vegetable oils.

APPLICATION

Alkylate gasoline is good for all small engines. For 2 stroke engines.

Alkylate gasoline is good for all small engines. For 4 stroke engines.

Racing fuel is good for all perfomance engines like gokarts, motorcykles and cars.

HVO Diesel is good for all diesel engines.

BIO Chain saw oil is good for all types of saw chains and swords. Works for both fuelpowered and power tools.

PACKAGING

Can	5 ltr. / 25 ltr.
Drum	200 ltr.
IBC	1.000 ltr.
Bulk	

Can	5 ltr. / 25 ltr.
Drum	200 ltr.
IBC	1.000 ltr.
Bulk	

Can 25L + Drum (200ltr) + Bulk.

Can 25L + Drum + Bulk.

Can 1ltr./4ltr./25ltr. + Drum + Bulk.





PRODUCT	DESCRIPTION	APPLICATION	PACKAGING
Propycool	Propylene glycol based heat transfer fluid	Propycool is used as a heat transfer fluid in cooling-, chiller- and HVAC systems.	Can 20 ltr. / 60 ltr Drum 200 ltr IBC 1.000 ltr Bulk
Citrec F	Propylene glycol based heat transfer fluid (Food)	Zitrec F is found acceptable by NSF International for use as a heat transfer fluid where there is the possiblity of incidental food contact.	Can .20 ltr Drum .200 ltr IBC 1.000 ltr Bulk
Etycool	Ethylene glycol based heat transfer fluid	Etycool is used as a heat transfer fluid in cooling-, chiller- and HVAC systems.	Can 20 ltr. / 60 ltr. Drum 200 ltr. IBC 1.000 ltr. Bulk
Alcocool KBS	Denaturated alchohol	Ethanol based heat transfer fluid made for geothermal heating and cooling.	Can .25 ltr. Drum .208 ltr. IBC 1.000 ltr. Bulk
Hycool	Potassium formate based coolant	Hycool is used as a heat transfer fluid in cooling-, chiller- and HVAC systems.	IBC1.000 ltr.
R32 R134a R404A R410A R407C R449A	Hydroflourcarbon refrigarant gas	Refrigerant gases for systems with high, medium and low tempetures.	Cylinder 5 kg. / 10 kg. / 50 kg. / 800 kg.
R290 R600a	Propane Isobutane	A natural refrigerant suitable for use in a range of refrigeration and airconditioning systems.	Cylinder5 kg.
Ammonia 99,9%	Ammonia anhydrous Chemical name: NH3	Refrigerant gas for systems with high, medium and low tempetures.	Cylinder 10 kg. / 40 kg. / 80 kg. Bulk



Automotive

CARCOOLANT

PRODUCT	DESCRIPTION	APPLICATION	PACKAGING
Coolant BS6580	Standard BS6580 grade. OAT Inhibitor.	BS coolant is an economical coolant concentrate providing frost and corrosion protection. Free from potentially harmful additives such as nitrites, amines and phosphate. Meets BS 6580 standard.	Can
Coolant Longlife	Longlife coolant. OAT Inhibitor.	Longlife coolant is an economical coolant concentrate providing frost and corrosion protection. Meets the approval specification of most major OEM's.	Can
Coolant OEM 774C	OEM quality approved for several major OEM's. Key approvals: BMW, GM, VW.	774C is a previous generation automotive coolant approved by a large number of car and heavy duty OEM. Technology: Combination of mineral (silicate/borate/nitrate) and organic inhibitors.	Can
Coolant OEM 774F	OEM quality approved for several major OEM's. Key approvals: Jaguar Land Rover, VW, GM, Ford.	Based on patended silicate-free additive techology, OEM 774F provides longlife corrosion protection for all engine metals, including aluminium and ferrous alloys. Technology: Organic inhibitors.	Can
Coolant OEM 774G	OEM quality approved for several major OEM's. Key approvals: VW	774G is recommended for high-tech engines, where high temperatue aluminimum protection is important. Technology: Combination of OAT technology with low silicate content.	Can

SCREENWASH

PRODUCT	DESCRIPTION	APPLICATION	PACKAGING
SW Bulk	Denaturated ethanol 96% Uncolored	For production of screenwash.	Bulk
Screenwash -75	Screenwash ready for dilution/use. Includes coloring, parfume and surfactants	Concentrated screenwash suitable for all makes and models. Keeps your windscreen clean.	Can
Screenwash -21	Screenwash ready for use. Includes coloring, parfume and surfactants	Screenwash ready to use. Suitable for all makes and models. Keeps your windscreen clean.	Can
Screenwash -18	Screenwash ready for use. Includes coloring, parfume and surfactants	Screenwash ready to use. Suitable for all makes and models. Keeps your windscreen clean.	Can 25 ltr. Drum 200 ltr. IBC 1.000 ltr. Bulk



About Brenntag

Brenntag, the global market leader in chemical distribution, covers all major markets with its extensive product and service portfolio. Headquartered in Essen, Germany, the company operates a global network with more than 670 locations in 77 countries. In 2020, the company, which has a global workforce of more than 17,000 employees, generated sales of EUR 11.8 billion.

Brenntag connects chemical manufacturers and chemical users. The company supports its customers and suppliers with tailor-made distribution solutions for industrial and specialty chemicals. With over 10,000 products and a world-class supplier base, Brenntag offers one-stop-shop solutions to around 185,000 customers. This includes specific application technology, an extensive technical support and value-added services such as just-in-time delivery, product mixing, formulation, repackaging, inventory management and drum return handling.

Long-standing experience and local excellence in the individual countries characterize the global market leader for chemical distribution.



DENMARK Brenntag Nordic A/S

Borupvang 5B 2750 Ballerup Tel: +45 43 29 28 00

FINLAND Brenntag Nordic Oy

Äyritie 16 01510 Vantaa Tel: +358 9 549 56 40

NORWAY Brenntag Nordic AS

Kalnesveien 1 1712 Grålum Tel: +47 69 10 25 00

SWEDEN Brenntag Nordic AB

Hyllie Boulevard 34 Hyllie Stationstorg 31 215 32 Malmö Tel: +46 40 28 73 00